Kleenscreen

Sanitized Actifresh

A solar screen that inhibits the development of **bacterial odors** as well as the growth of **mold** and **mildew**





In the home Alloy | Graphite

(III



Keeping fit Canyon | Raven

At work Barley | Graphite

1

TT

ant)

H


Ŧ

Dining out Black | Pure White

lenter C.

- the main





Education Alloy | Pure white

Kleenscreen



Fabric Overview

What is Kleenscreen?

Kleenscreen is Texstyle's newest solar screen fabric and is made with Sanitized[®] antimicrobial material protection. It is available in three openness factors, two widths, and has a modern neutral color palette.

What is the Sanitized[®] hygiene function?

The Sanitized" hygiene function is added to the fabric during manufacturing and protects the fabric surface from the formation of fungi (including mold and mildew) and bacterial odors, providing long lasting material protection.

How does Sanitized[®] Protection increase the life span of the product?

By fighting the growth of microbes on the surface of the fabric, the product is continuously cleaner and less at risk of degradation from bacteria, staining, mold and mildew.

Should I still clean my product as required?

Yes, Sanitized^{*} protection will not be impacted by recommended product care and cleaning instructions. Normal cleaning and care practices should be maintained and are available at texstyle.com

How long does the Sanitized[®] protection last?

The Sanitized^{*} material protection is built in as a critical part of the manufacturing process of Kleenscreen, and as such will not wash or wear away. Kleenscreen is manufactured to maintain ongoing protection for the useful lifetime of the product.

Why should you choose Kleenscreen with Sanitized?

- Sanitized[®] products are available globally and provide the best anti-microbial material protection using the best available technology
- OekoTex[®] 100 and Greenguard Gold certifications assure that no harmful ingredients are used in the fabric

Kleenscreen

Technical Data

	1%	3%	5%						
Composition	26% Polyester / 74% PVC								
Openness Factor	Average 1%	Average 3%	Average 5%						
Weight	14.25 oz/yd2 (483g/m²)	14.01 oz/yd2 (475g/m²)	13.12 oz/yd2 (445g/m²)						
Thickness	0.024in (.60mm)	0.022in (.56mm)	0.022in (.56mm)						
Light Fastness	Grade 4 out of 5 (AATCC 16)								
Average Length	33 yd/roll (30m)								
Width	98.4" (2.5m), 118" (3m)								
Railroadable	Test first. All fabrics in the room should be cut the same direction to avoid visual variation.								
Fire Classifications	NFPA 701								
Fungal/Bacterial Resistance	ASTM G21 and ASTM E2180								
Environmental Standards	Greenguard Gold, Health Product Declaration, Oeko-Tex Standard 100, ISO 14001								





ROLLER

PANEL





10 YEAR WARRANTY



FR









HEALTH PRODUCT DECLARATION PRINTABLE



Solar Properties

Color	Fabric Properties						Fabric & Glass	
	Thermal			Optical		OF	SHGC %	SHGC
	Rs(%)	As(%)	Ts(%)	Rv(%)	Tv(%)		Improvement	
Kleenscreen 1%								
Barley	68	23	9	71	7	1	50	0.18
Black	3	96	1	3	1	1	56	0.35
Graphite	10	89	1	11	1	1	59	0.37
Pure White	65	17	18	71	16	1	52	0.23
Alloy	57	35	8	61	6	1	52	0.21
Canyon	21	71	8	20	6	1	57	0.33
Raven	10	88	2	9	2	1	58	0.34
Ash	22	75	3	23	2	1	56	0.31
Kleenscreen 3%								
Barley	62	24	14	65	12	3	52	0.22
Black	4	91	5	4	6	3	59	0.37
Graphite	13	81	6	14	6	3	58	0.34
Pure White	63	16	21	69	19	3	52	0.25
Alloy	9	80	11	8	9	3	59	0.38
Canyon	19	73	8	19	6	3	57	0.33
Raven	9	86	5	8	5	3	59	0.35
Ash	24	69	7	24	6	3	57	0.32
Kleenscreen 5%								
Barley	62	23	15	65	13	5	52	0.23
Black	4	90	6	4	6	5	59	0.37
Graphite	12	81	7	13	7	5	58	0.35
Pure White	62	16	22	67	21	5	53	0.26
Alloy	53	33	14	56	12	5	53	0.25
Canyon	19	71	10	19	9	5	58	0.34
Raven	9	84	7	8	7	5	59	0.36
Ash	23	68	9	23	8	5	57	0.33





Kleenscreen with Sanitized[®] inhibits the development of bacterial odors as well as the growth of mold and mildew.

This unique antimicrobial material enhances the functionality and performance of your shades for comfort and peace of mind.

Kleenscreen is available in 8 colors, with 1% | 3% | 5% openness and 98" or 118" roll widths.



P 1 800 552 5100 E info@texstyle.com

Learn more at texstyle.com

